



**NEW!**



C15-Series



S10/S15-Series



T10-Series



T15-Series



T20-Series

**NEW!**



T30-Series



M-Series

# HOSE REELS FOR ALL NEEDS

FOR OIL • GREASE • AIR • WATER • ANTI FREEZE • WIND SCREEN FLUID

# HOSE REELS

MANUFACTURING AND DEVELOPMENT WITH THE LATEST TECHNOLOGY

## C15-SERIES CASED REELS



- The new series C15 features the same ball bearing supported composite spool as the S-series
- The exclusive design offers optimum operation in any mounting position such as wall, ceiling, floor or tank.
- C15 cased hose reels are ideal for use with oil, diesel, grease, air, water, antifreeze, wind screen fluid etc.
- Hose capacity from 10 to 15m with 1/2" hose.

PART NO	FLUID	HOSE	Ø	MPa	CONNECTION IN - OUT
17740	Oil / Anti freeze	10 m	1/2"	7,5	BSP 1/2" (M) - 1/2" (M)
17743	Oil / Anti freeze	15 m	1/2"	7,5	BSP 1/2" (M) - 1/2" (M)
27740	Grease	15 m	3/8"	35	BSP 3/8" (M) - 1/4" (M)
37754	Wind screen	15 m	1/2"	1,5	BSP 1/2" (M) - 1/2" (M)
37769	Air / Water	15 m	3/8"	1,5	BSP 1/2" (M) - 1/2" (M)
37770	Air / Water	15 m	1/2"	1,5	BSP 1/2" (M) - 1/2" (M)
37750	H.P. Water*	15 m	3/8"	18	BSP 3/8" (M) - 3/8" (M)
17744	Oil / Anti freeze	Without hose		7,5	BSP 1/2" (M) - 1/2" (M)
27741	Grease	Without hose		35	BSP 3/8" (M) - 3/8" (M)
37755	Wind screen	Without hose		1,5	BSP 1/2" (M) - 1/2" (M)
37751	H.P. Water*	Without hose		18	BSP 1/2" (M) - 3/8" (M)

\*Max. temp. +150°C. Do not use max. temp. and max pressure at the same time.

## S10-SERIES OPEN REELS



- Premium single arm reel, featuring a multi-position guide arm, a fully enclosed drive spring and ball bearing supported composite spool.
- The new reel require less power to pull out and rewind the hose, which makes the job easier for the user.
- The reel can be mounted in any position. The overall package is light and easy to install.
- The arm and the base are made of die-casted aluminium, which offer a rigid and highly corrosion resistant reel.
- For use with oil, diesel, grease, air, water, antifreeze, wind screen fluid etc.
- Hose capacity 15m with 3/8" and 1/2" hose.

PART NO	FLUID	HOSE	Ø	MPa	CONNECTION IN - OUT
17720	Oil / Anti freeze	10 m	1/2"	7,5	BSP 1/2" (M) - 1/2" (M)
27736	Grease	10 m	3/8"	35	BSP 1/4" (M) - 1/4" (M)
37766	Air / Water	10 m	3/8"	1,5	BSP 1/2" (F) - 3/8" (M)
37767	Air / Water	10 m	1/2"	1,5	BSP 1/2" (F) - 1/2" (M)
37738	Degreaser, Screenfluid	10 m	1/2"	1,5	BSP 1/2" (F) - 1/2" (F)
37733	H.P. Water*	10 m	3/8"	18	BSP 3/8" (M) - 3/8" (M)
17723	Oil / Air / Water	Without hose (10m)		7,5	BSP 1/2" (M) - 1/2" (F)
27737	Grease	Without hose (10m)		35	BSP 1/2" (M) - 3/8" (F)
37739	Degreaser, Screenfluid	Without hose (10m)		1,5	BSP 1/2" (M) - 1/2" (F)
37734	H.P. Water*	Without hose (10m)		18	BSP 1/2" (M) - 1/2" (F)

\*Max. temp. +150°C. Do not use max. temp. and max pressure at the same time.

## S15-SERIES OPEN REELS



PART NO	FLUID	HOSE	Ø	MPa	CONNECTION IN - OUT
17737	Oil / Anti freeze	15 m	1/2"	7,5	BSP 1/2" (M) - 1/2" (M)
27734	Grease	15 m	3/8"	35	BSP 1/4" (M) - 1/4" (M)
37764	Air / Water	15 m	3/8"	1,5	BSP 1/2" (F) - 3/8" (M)
37765	Air / Water	15 m	1/2"	1,5	BSP 1/2" (F) - 1/2" (M)
37736	Degreaser, Screenfluid	15 m	1/2"	1,5	BSP 1/2" (F) - 1/2" (F)
37728	H.P. Water*	15 m	3/8"	18	BSP 3/8" (M) - 3/8" (M)
17738	Oil / Air / Water	Without hose (15m)		7,5	BSP 1/2" (M) - 1/2" (F)
27735	Grease	Without hose (15m)		35	BSP 1/2" (M) - 3/8" (F)
37737	Degreaser, Screenfluid	Without hose (15m)		1,5	BSP 1/2" (M) - 1/2" (F)
37729	H.P. Water*	Without hose (15m)		18	BSP 1/2" (M) - 1/2" (F)

\*Max. temp. +150°C. Do not use max. temp. and max pressure at the same time.

# HOSE REELS

MANUFACTURING AND DEVELOPMENT WITH THE LATEST TECHNOLOGY

## T10-SERIES OPEN REELS – HEAVY DUTY



- The ideal hose reel for all general applications for use with oil, diesel, grease, air, water, antifreeze etc.
- The reels are compact and flexible for optimum operation in any mounting position such as wall, ceiling, floor or tank.
- Hose capacity from 10m x 1/4" hose to 10m x 1/2" hose with T10-series and 15m x 1/4" to 15m x 1/2" with T15-series reels.
- The all-steel drum and base are powder coated. All other parts are zinc-plated.
- Spring unit fully enclosed and lubricated.

PART NO	FLUID	HOSE	Ø	MPa	CONNECTION IN - OUT
17730	Oil / Anti freeze	10m	1/2"	7,5	BSP 1/2" (F) - 1/2" (F)
27730	Grease	10 m	1/4"	35	BSP 1/4" (F) - 1/4" (F)
37760	Air / Water	10 m	3/8"	1,5	ø 9mm - ø 9mm
17731	Oil / Anti freeze	Without hose		7,5	BSP 1/2" (F) - 3/8" (F)
27731	Grease	Without hose		35	BSP 1/2" (F) - 3/8" (F)
37761	Air / Water	Without hose		1,5	BSP 1/2" (F) - 3/8" (F)

## T15-SERIES OPEN REELS – HEAVY DUTY



PART NO	FLUID	HOSE	Ø	MPa	CONNECTION IN - OUT
17732	Oil / Anti freeze	15 m	1/2"	7,5	BSP 1/2" (F) - 1/2" (F)
27732	Grease	15 m	1/4"	35	BSP 1/4" (F) - 1/4" (F)
37762	Air / Water	15 m	1/2"	1,5	ø 11mm - ø 11 mm
37752	H.P. Water*	15 m	3/8"	18	BSP 3/8" (F) - 3/8" (F)
<small>*Max. temp. +150°C. Do not use max. temp. and max pressure at the same time.</small>					
17733	Oil / Anti freeze	Without hose		7,5	BSP 1/2" (F) - 3/8" (F)
27733	Grease	Without hose		35	BSP 1/2" (F) - 3/8" (F)
37763	Air / Water	Without hose		1,5	BSP 1/2" (F) - 3/8" (F)

## T20-SERIES OPEN REELS – HEAVY DUTY



- A compact and flexible all-steel 15m x 3/4" hose reel.
- Full port 3/4" shaft and swivel for no flow restrictions.
- An ideal reel for high volume use with oil, diesel, air, water etc.
- Optimum operation in any mounting position such as wall, ceiling, floor or tank.
- Hose capacity 20m with 1/2" hose or 15m with 3/4" hose.
- The drum and base are powder coated. All other parts are zinc-plated.
- Spring unit fully enclosed and lubricated.

PART NO	FLUID	HOSE	Ø	MPa	CONNECTION IN - OUT
17734	Oil / Diesel/ Anti freeze	20 m	1/2"	7,5	BSP 1/2" (F) - 1/2" (F)
17736	Oil / Diesel/ Anti freeze	15 m	3/4"	7,5	BSP 3/4" (F) - 3/4" (F)
37744	Air / Water	20 m	1/2"	1,5	ø 11mm - ø 11mm
37746	Air / Water	15 m	3/4"	1,5	ø 19mm - ø 19mm
37745	All above fluids	Without hose		7,5	BSP 3/4" (F) - 3/4" (F)

## T30-SERIES OPEN REELS – HEAVY DUTY



- A new compact series high volume, all-steel, heavy duty reels.
- An ideal reel for high volume use with oil, diesel, air, water etc.
- Ball bearing supported spool to minimize the force needed to pull out the hose.
- 1" Full port, zero flow restrictions.
- Hose capacity ranges from 15 m with 1" hose to 30 m with 1/2" hose.
- The drum and base are powder coated and the base is welded 4mm steel.

PART NO	FLUID	HOSE	Ø	MPa	CONNECTION IN - OUT
17780	Oil / Diesel/ Anti freeze	30 m	1/2"	7,5	BSP 1/2" (F) - 1/2" (F)
17781	Oil / Diesel/ Anti freeze	25 m	3/4"	7,5	BSP 3/4" (F) - 3/4" (F)
17782	Oil / Diesel/ Anti freeze	15 m	1"	7,5	BSP 1" (F) - 1" (F)
37780	Air / Water	30 m	1/2"	1,5	BSP 1/2" (F) - 1/2" (F)
37782	Air / Water	15 m	1"	1,5	BSP 1" (F) - 1" (F)
17779	All above fluids	Without hose		7,5	BSP 1" (M) - 1" (F)

## M-SERIES CASED REELS



- The ideal hose reel for all general applications for use with air and water.
- The reels are compact and flexible for optimum operation in any mounting position such as wall, ceiling, floor or tank.

PART NO	FLUID	HOSE	Ø	MPa	CONNECTION IN - OUT
37730	Air / Water	12m	5/16"	2	BSP 3/8" (M) - 1/4" (M)
37731	Air / Water	10m	3/8"	2	BSP 3/8" (M) - 1/4" (M)

## ACCESSORIES FOR HOSE REELS



**MOUNTING PLATE  
FOR 3-5 REELS**



**SWING  
BRACKET**



**REEL POST  
3-5 REELS**



**SERVICE STAND  
3 REELS**



**SERVICE STAND  
6 REELS**



**SERVICE STAND  
16 REELS**



## FULL RANGE OF ACCESSORIES



**DIGITAL  
METERS**



**MULTI-FLUID  
GUN**



**GREASE GUNS  
& METERS**



**CABLE  
REELS**

## EUROLUBE EQUIPMENT AB

Stråsavägen 2, SE-711 76 Storå, Sweden

EMAIL [eurolube@eurolube.com](mailto:eurolube@eurolube.com) PHONE +46 581 836 65 FAX +46 581 409 75