



2009-02
HOSE REELS



T20-Series

T15-Series

S10/S15-Series

T10-Series

C12-Series

M-Series

HOSE REELS FOR ALL NEEDS

FOR OIL • GREASE • AIR • WATER • ANTI FREEZE • WIND SCREEN FLUID

MANUFACTURING AND DEVELOPMENT WITH THE LATEST TECHNOLOGY

 www.eurolube.com

HOSE REELS

MANUFACTURING AND DEVELOPMENT WITH THE LATEST TECHNOLOGY

C12-SERIES CASED REELS



- The exclusive design offers optimum operation in any mounting position such as wall, ceiling, floor or tank.
- C12 cased hose reels are ideal for use with oil, diesel, grease, air, water, antifreeze, wind screen fluid etc.
- Hose capacity from 10m with 1/2" hose up to 12m with 3/8" hose.
- The casing is made of die-casted aluminium and is powder coated.
- Spring unit fully enclosed and lubricated.

PART NO	FLUID	HOSE	Ø	MPa	CONNECTION IN - OUT
17742	Oil / Anti freeze	10 m	1/2"	7,5	BSP 1/2" (M) - 1/2" (M)
27748	Grease	12 m	1/4"	35	BSP 1/4" (M) - 1/4" (M)
37740	Wind screen	10 m	1/2"	1,5	ø 11mm - ø 11mm
37741	Air / Water	12 m	3/8"	1,5	ø 9mm - ø 9mm
37742	Air / Water	10 m	1/2"	1,5	ø 11mm - ø 11mm
37749	H.P. Water*	12 m	3/8"	18	BSP 3/8" (M) - 3/8" (M)
17741	Oil / Anti freeze	Without hose		7,5	BSP 1/2" (F) - 3/8" (F)
27747	Grease	Without hose		35	BSP 1/2" (F) - 3/8" (F)
37743	Wind screen	Without hose		1,5	BSP 1/2" (F) - 3/8" (F)
37748	H.P. Water*	Without hose		18	BSP 1/2" (F) - 3/8" (F)

*Max. temp. +150°C. Do not use max. temp. and max pressure at the same time.

T10-SERIES OPEN REELS



- The ideal hose reel for all general applications for use with oil, diesel, grease, air, water, antifreeze etc.
- The reels are compact and flexible for optimum operation in any mounting position such as wall, ceiling, floor or tank.
- Hose capacity from 10m with 1/4" hose to 10m with 1/2" hose. The drum and base are powder coated. All other parts are zinc-plated.
- Spring unit fully enclosed and lubricated.

PART NO	FLUID	HOSE	Ø	MPa	CONNECTION IN - OUT
17730	Oil / Anti freeze	10m	1/2"	7,5	BSP 1/2" (F) - 1/2" (F)
27730	Grease	10 m	1/4"	35	BSP 1/4" (F) - 1/4" (F)
37760	Air / Water	10 m	3/8"	1,5	ø 9mm - ø 9mm
17731	Oil / Anti freeze	Without hose		7,5	BSP 1/2" (F) - 3/8" (F)
27731	Grease	Without hose		35	BSP 1/2" (F) - 3/8" (F)
37761	Air / Water	Without hose		1,5	BSP 1/2" (F) - 3/8" (F)

M-SERIES CASED REELS



- The ideal hose reel for all general applications for use with air and water.
- The reels are compact and flexible for optimum operation in any mounting position such as wall, ceiling, floor or tank.

PART NO	FLUID	HOSE	Ø	MPa	CONNECTION IN - OUT
37730	Air / Water	12m	5/16"	2	BSP 3/8" (M) - 1/4" (M)
37731	Air / Water	10m	3/8"	2	BSP 3/8" (M) - 1/4" (M)

HOSE REELS

MANUFACTURING AND DEVELOPMENT WITH THE LATEST TECHNOLOGY

S10-SERIES OPEN REELS



- Eurolube introduce the new S10 and S15 premium single arm reel, featuring a multi-position guide arm, a fully enclosed drive spring and ball bearing supported composite spool.
- The new reel require less power to pull out and rewind the hose, which makes the job easier for the user.
- The reel can be mounted in any position. The overall package is light and easy to install.
- The arm and the base are made of die-casted aluminium, which offer a rigid and highly corrosion resistant reel.
- For use with oil, diesel, grease, air, water, antifreeze, wind screen fluid etc.
- Hose capacity 15m with 3/8" and 1/2" hose.

PART NO	FLUID	HOSE	Ø	MPa	CONNECTION IN - OUT
17720	Oil / Anti freeze	10 m	1/2"	7,5	BSP 1/2" (M) - 1/2" (M)
27736	Grease	10 m	3/8"	35	BSP 1/4" (M) - 1/4" (M)
37766	Air / Water	10 m	3/8"	1,5	BSP 1/2" (F) - 3/8" (M)
37767	Air / Water	10 m	1/2"	1,5	BSP 1/2" (F) - 1/2" (M)
37738	Degreaser, Screenfluid	10 m	1/2"	1,5	BSP 1/2" (F) - 1/2" (F)
37733	H.P. Water*	10 m	3/8"	18	BSP 3/8" (M) - 3/8" (M)
17723	Oil / Air / Water	Without hose (10m)		7,5	BSP 1/2" (M) - 1/2" (F)
27737	Grease	Without hose (10m)		35	BSP 1/2" (M) - 3/8" (F)
37739	Degreaser, Screenfluid	Without hose (10m)		1,5	BSP 1/2" (M) - 1/2" (F)
37734	H.P. Water*	Without hose (10m)		18	BSP 1/2" (M) - 1/2" (F)

*Max. temp. +150°C. Do not use max. temp. and max pressure at the same time.

S15-SERIES OPEN REELS



PART NO	FLUID	HOSE	Ø	MPa	CONNECTION IN - OUT
17737	Oil / Anti freeze	15 m	1/2"	7,5	BSP 1/2" (M) - 1/2" (M)
27734	Grease	15 m	3/8"	35	BSP 1/4" (M) - 1/4" (M)
37764	Air / Water	15 m	3/8"	1,5	BSP 1/2" (F) - 3/8" (M)
37765	Air / Water	15 m	1/2"	1,5	BSP 1/2" (F) - 1/2" (M)
37736	Degreaser, Screenfluid	15 m	1/2"	1,5	BSP 1/2" (F) - 1/2" (F)
37728	H.P. Water*	15 m	3/8"	18	BSP 3/8" (M) - 3/8" (M)
17738	Oil / Air / Water	Without hose (15m)		7,5	BSP 1/2" (M) - 1/2" (F)
27735	Grease	Without hose (15m)		35	BSP 1/2" (M) - 3/8" (F)
37737	Degreaser, Screenfluid	Without hose (15m)		1,5	BSP 1/2" (M) - 1/2" (F)
37729	H.P. Water*	Without hose (15m)		18	BSP 1/2" (M) - 1/2" (F)

*Max. temp. +150°C. Do not use max. temp. and max pressure at the same time.

T15-SERIES OPEN REELS



- The ideal hose reel for all general applications for use with oil, diesel, grease, air, water, antifreeze etc.
- The reels are compact and flexible for optimum operation in any mounting position such as wall, ceiling, floor or tank.
- Hose capacity from 15m with 1/4" hose to 15m with 1/2" hose. The drum and base are powder coated. All other parts are zinc-plated.
- Spring unit fully enclosed and lubricated.

PART NO	FLUID	HOSE	Ø	MPa	CONNECTION IN - OUT
17732	Oil / Anti freeze	15 m	1/2"	7,5	BSP 1/2" (F) - 1/2" (F)
27732	Grease	15 m	1/4"	35	BSP 1/4" (F) - 1/4" (F)
37762	Air / Water	15 m	1/2"	1,5	ø11mm - ø11 mm
37752	H.P. Water*	15 m	3/8"	18	BSP 3/8" (F) - 3/8" (F)
17733	Oil / Anti freeze	Without hose		7,5	BSP 1/2" (F) - 3/8" (F)
27733	Grease	Without hose		35	BSP 1/2" (F) - 3/8" (F)
37763	Air / Water	Without hose		1,5	BSP 1/2" (F) - 3/8" (F)

*Max. temp. +150°C. Do not use max. temp. and max pressure at the same time.

T20-SERIES OPEN REELS



- A compact and flexible 15m x 3/4" hose reel.
- Full port 3/4" shaft and swivel for no flow restrictions.
- An ideal reel for high volume use with oil, diesel, air, water etc.
- Optimum operation in any mounting position such as wall, ceiling, floor or tank.
- Hose capacity 20m with 1/2" hose or 15m with 3/4" hose.
- The drum and base are powder coated. All other parts are zinc-plated.
- Spring unit fully enclosed and lubricated.

PART NO	FLUID	HOSE	Ø	MPa	CONNECTION IN - OUT
17734	Oil / Anti freeze	20 m	1/2"	7,5	BSP 1/2" (F) - 1/2" (F)
17736	Oil / Anti freeze	15 m	3/4"	7,5	BSP 3/4" (F) - 3/4" (F)
37744	Air / Water	20 m	1/2"	1,5	ø 11mm - ø 11mm
37746	Air / Water	15 m	3/4"	1,5	ø 19mm - ø 19mm
37745	All above fluids	Without hose		7,5	BSP 3/4" (F) - 3/4" (F)

T10-SERIES



FOR OIL AND ANTIFREEZE

EXAMPLE OF HOSE REEL KITS FOR OIL, ANTIFREEZE, GREASE AND SCREEN FLUID

C12-SERIES



FOR OIL AND ANTIFREEZE



FOR GREASE



FOR WIND SCREEN FLUID

S10 / S15-SERIES



FOR OIL, DIESEL AND ANTIFREEZE



FOR GREASE



FOR WIND SCREEN FLUID

T15-SERIES



FOR OIL, DIESEL AND ANTIFREEZE

T20-SERIES



FOR OIL, DIESEL AND ANTIFREEZE

For detailed information about our reel kits, please visit www.eurolube.com or ask for our catalogue.



FULL RANGE OF OIL GUNS, METERS, CONTROL VALVES ETC. FOR REELS



EUROLUBE EQUIPMENT AB

Stråsavägen 2, SE-711 76 Storå, Sweden

EMAIL eurolube@eurolube.com PHONE +46 581 836 65 FAX +46 581 409 75