



ED30 DIAPHRAGM PUMP MIX PP

MANUFACTURE AND DEVELOPMENT USING THE LATEST TECHNOLOGY

WWW.EUROLUBE.COM

ED30 DIAPHRAGM PUMP MIX PP

Probably the most environmentally friendly pump on the market. Less pollution thanks to lubrication-free air motor, which requires less energy and gives greater efficiency. UNIQUE AIR VALVE. Unique patented frictionless oscillating air valve, which gives up to 20 times faster switching time compared to conventional valves.

Advantage: Greatly reduced pulsation. Few parts thanks to our unique design. Only one moving part in the entire air valve. Pumps up to 3mm particles in the fluid.

Exceptional self priming, up to 8 m. Easy to install and fast maintenance, all wear parts can be replaced without disconnecting the pump. Max air pressure: 0,7 MPA

Pressure ratio: 1:1. Air inlet: 3/8" BSP (F). Fluid inlet: 2x3/8" BSP (F) Fluid outlet: 1/2" BSP (F) plus flange. Capacity: 30 l/minute. Max solids: 3 mm. Pump Body: Polypropylene

Seals: Viton. Check valve: Acetal. Diaphragm: Hytrel

TECHNICAL DATA

Part No	11743
Capacity	38 l/min
Air connection	3/8" (F) BSP
Maximum air pressure	0,7 (7) MPa (bar)
Maximum temperature	80 °C
Seals	Viton
Material pump body	Polypropylene
Material diaphragm	Hytrel
Material balls	Acetal
Connection	2x3/8" - 1/2" (F)-(F) BSP
Packaging LxWxH	0,22 x 0,22 x 0,22 m
Weight (Gross)	3 kg
H.S. Code	84135080



EUROLUBE EQUIPMENT

by Alentec & Orion AB, Grustagsvägen 4, SE-138 40 Älta, Sweden

EMAIL eurolube@alentec.se

PHONE +46 (0)8-747 67 10

FAX +46 (0)8-715 20 74

 www.eurolube.com