



## ED50 DIAPHRAGM PUMP MIX PP 2X3/8" - 1/2" (F)-(F) BSP

MANUFACTURE AND DEVELOPMENT USING THE LATEST TECHNOLOGY

 [WWW.EUROLUBE.COM](http://WWW.EUROLUBE.COM)

## ED50 DIAPHRAGM PUMP MIX PP 2X3/8" - 1/2" (F)-(F) BSP

Probably the most environmentally friendly pump on the market. Less pollution thanks to lubrication-free air motor, which requires less energy and gives greater efficiency. Unique patented frictionless oscillating air valve, which gives up to 20 times faster switching time compared to conventional valves. Advantage: Greatly reduced pulsation. Few parts thanks to our unique design. Only one moving part in the entire air valve. Note! Should not be used to mix fluids with differing viscosities.

### TECHNICAL DATA

Part No	11738
Capacity	50 l/min free flow
Air connection	3/8" (F) BSP
Maximum air pressure	0,7 (7) MPa (bar)
Maximum temperature	70 °C
Seals	Viton
Material pump body	Polypropylene
Material diaphragm	Hytrel
Material balls	PTFE
Connection	2x3/8" - 1/2" (F)-(F) BSP
Packaging LxWxH	0,22 x 0,22 x 0,22 m
Weight (Gross)	3,3 kg
H.S. Code	84135080



## EUROLUBE EQUIPMENT

by Alentec & Orion AB, Grustagsvägen 4, SE-138 40 Älta, Sweden

EMAIL [\\*eurolube@alentec.se](mailto:*eurolube@alentec.se)

PHONE +46 (0)8-747 67 10

FAX +46 (0)8-715 20 74

 [www.eurolube.com](http://www.eurolube.com)