



ED50 DIAPHRAGM PUMP STAINLESS STEEL 1/2" - 1/2" (F)-(F) BSP

MANUFACTURE AND DEVELOPMENT USING THE LATEST TECHNOLOGY

 WWW.EUROLUBE.COM

ED50 DIAPHRAGM PUMP STAINLESS STEEL 1/2" - 1/2" (F)-(F) BSP

Probably the most environmentally friendly pump on the market. Less pollution thanks to lubrication-free air motor, which requires less energy and gives greater efficiency.

UNIQUE AIR VALVE

Unique patented frictionless oscillating air valve, which gives up to 20 times faster switching time compared to conventional valves.

Advantage:

Greatly reduced pulsation.

Few parts thanks to our unique design.

Only one moving part in the entire air valve.

Pumps up to 3mm particles in the fluid.

Exceptional self priming, up to 8 m.

Easy to install and fast maintenance, all wear parts can be replaced without disconnecting the pump. Max air pressure: 0,7 MPA

Pressure ratio: 1:1

Air inlet: 3/8" BSP (F)

Fluid inlet: 1/2" BSP (F) plus flange

Fluid outlet: 1/2" BSP (F) plus flange

Capacity: 50l/minute

Max solids: 3 mm

Pump Body: Stainless steel

Seals: EPDM

Check valve: Hytrel

Diaphragm: Hytrel

TECHNICAL DATA

Part No	11756
Media	Windscreen fluid/AdBlue®
Capacity	50 l/min
Air connection	3/8" (F) BSP
Maximum air pressure	0,7 (7) MPa (bar)
Maximum temperature	°C
Seals	EPDM
Material pump body	Stainless steel (AISI 316)
Material diaphragm	TPE / Hytrel®
Material balls	TPE / Hytrel®
Connection	1/2" - 1/2" (F)-(F) BSP
Packaging LxWxH	0,22 x 0,22 x 0,23 m
Weight (Gross)	8 kg
H.S. Code	84138100



EUROLUBE EQUIPMENT

by Alentec & Orion AB, Grustagsvägen 4, SE-138 40 Älta, Sweden

EMAIL eurolube@alentec.se

PHONE +46 (0)8-747 67 10

FAX +46 (0)8-715 20 74

 www.eurolube.com