



## **NEX-U® U-VALVE+ FLOW CONTROL UNIT WITH BLUETOOTH AND WIFI 1/2" (F)-(F) BSP**

## NEX·U® U-VALVE+ FLOW CONTROL UNIT WITH BLUETOOTH AND WIFI 1/2" (F)-(F) BSP

U-valve combines in a compact unit a high accuracy pulse meter, a solenoid valve and a large and cleanable fluid screen filter with the electronics required to control the meter and valve operation and to communicate with other system components. Reduces installation time and eliminates the risk of leak when using separate components. It has a large, high visibility LED display showing the U-valve number assigned in the system, four colored LED lights that show the U-valve operation for diagnosis and two buttons for system configuration. U-valve supports Can-bus cable communication that transmits data and the electric power required to open the solenoid valve. Supports Wi-Fi® to communicate with other system components. It also supports Bluetooth® communications for connecting with a U-vision or a U-vision+ fluid handle with display. Requires 24 V DC supplied by a U-dat or a U-power module. U-valve+ wired connections use fast connection in/out Can-bus terminals.

### TECHNICAL DATA

Part No	53851
Connection	1/2" (F)-(F) BSP
H.S. Code	90261021



### EUROLUBE EQUIPMENT

by Alentec & Orion AB, Grustagsvägen 4, SE-138 40 Älta, Sweden

EMAIL [\\*eurolube@alentec.se](mailto:*eurolube@alentec.se)

PHONE +46 (0)8-747 67 10

FAX +46 (0)8-715 20 74

 [www.eurolube.com](http://www.eurolube.com)