



AUTOVAC 57 MOBILE EXTRACTION PUMP

AUTOVAC 57 MOBILE EXTRACTION PUMP

Model 317-57, the mobil unit is ideal to extract oil or diesel from engines and tanks directly to a 200l drum for later disposal. The pump is designed to deliver maximum vaccum, up to 85%. The suction tube is equipped with a large strainer and vacuum meter to indicate that the fluid has been emptied. Includes connectors and probes for efficient extraction.Min. air pressure 3 bar, Max. air pressure 7 bar, Recomended air pressure 4-5 bar

Max. vaccum -0,85 bar, Max. temperature +95°C, Capacity, free flow 15 I / minute, Capacity with probes 2-10 I / minute,

Engine oil at minimum +70°C, see details in service manual

TECHNICAL DATA	
Part No	317-57
Maximum air pressure	0,7 (7) MPa (bar)
Packaging LxWxH	0,96 x 0,86 x 0,28 m
Weight (Gross)	31,5 kg



EUROLUBE EQUIPMENT

by Alentec & Orion AB, Grustagsvägen 4, SE-138 40 Älta, Sweden

EMAIL *eurolube@alentec.se PHONE **+46 (0)8-747 67 10** FAX **+46 (0)8-715 20 74**

