



ED100 DIAPHRAGM PUMP ALUMINIUM 1" - 1" (F)-(F) BSP

MANUFACTURE AND DEVELOPMENT USING THE LATEST TECHNOLOGY

[WWW.EUROLUBE.COM](http://www.eurolube.com)

ED100 DIAPHRAGM PUMP ALUMINIUM 1" - 1" (F)-(F) BSP

Probably the most environmentally friendly pump on the market. Less pollution thanks to lubrication-free air motor, which requires less energy and gives greater efficiency.

UNIQUE AIR VALVE

Unique patented frictionless oscillating air valve, which gives up to 20 times faster switching time compared to conventional valves.

Advantage:

Greatly reduced pulsation.

Few parts thanks to our unique design.

Only one moving part in the entire air valve.

Pumps up to 4mm particles in the fluid.

Exceptional self priming, up to 8 m.

Easy to install and fast maintenance, all wear parts can be replaced without disconnecting the pump. Max air pressure: 0,7 MPA

Pressure ratio: 1:1

Air inlet: 3/8" BSP (F)

Fluid inlet: 1" BSP (F) plus flange

Fluid outlet: 1" BSP (F) plus flange

Capacity: 100l/minute

Max solids: 4 mm

Pump Body: Aluminium

Seals: NBR

Check valve: Hytrel

Diaphragm: Hytrel

TECHNICAL DATA

Part No	11760
Capacity	100 l/min
Air connection	3/8" (F) BSP
Maximum air pressure	0,7 (7) MPa (bar)
Maximum temperature	80 °C
Seals	NBR
Material pump body	Aluminium
Material diaphragm	Hytrel
Material balls	Acetal
Connection	1" - 1" (F)-(F) BSP
Packaging LxWxH	0,27 x 0,25 x 0,27 m
Weight (Gross)	8 kg
H.S. Code	84135080



EUROLUBE EQUIPMENT

by Alentec & Orion AB, Grustagsvägen 4, SE-138 40 Älta, Sweden

EMAIL eurolube@alentec.se

PHONE +46 (0)8-747 67 10

FAX +46 (0)8-715 20 74

 www.eurolube.com