



**DIAPHRAGM PUMP 1/2" OIL/GLYCOL 54 L/MIN FREE
FLOW ATEX**

DIAPHRAGM PUMP 1/2" OIL/GLYCOL 54 L/MIN FREE FLOW ATEX

Air operated diaphragm pump for wall or floor installation. For non-corrosive liquids, oil, antifreeze, waste oil etc.

TECHNICAL DATA

Part No	11782
Ratio	1:1
Media	Oil/Glycol
Capacity	54 l/min free flow
Air connection	1/4" (F) NPSM
Maximum air pressure	0,8 (8) MPa (bar)
Inlet	1/2" (F) BSP
Outlet	1/2" (F) BSP
Max suction height	8 m
Max particle size	2,5 (3/32") mm (inch)
Material pump body	Aluminium
Material diaphragm	NBR / Buna-N
Material balls	NBR / Buna-N
Material ball valve seats	Aluminium
Certification	ATEX
Weight (Gross)	4,806 kg
H.S. Code	84138100



EUROLUBE EQUIPMENT

by Alentec & Orion AB, Grustagsvägen 4, SE-138 40 Älta, Sweden

EMAIL *eurolube@alentec.se

PHONE +46 (0)8-747 67 10

FAX +46 (0)8-715 20 74

 www.eurolube.com