



ED50 DIAPHRAGM PUMP PP 1/2" - 1/2" (F)-(F) BSP

MANUFACTURE AND DEVELOPMENT USING THE LATEST TECHNOLOGY

 WWW.EUROLUBE.COM

ED50 DIAPHRAGM PUMP PP 1/2" - 1/2" (F)-(F) BSP

Probably the most environmentally friendly pump on the market. Less pollution thanks to lubrication-free air motor, which requires less energy and gives greater efficiency. Unique patented frictionless oscillating air valve, which gives up to 20 times faster switching time compared to conventional valves. Advantage: Greatly reduced pulsation. Few parts thanks to our unique design. Only one moving part in the entire air valve.

TECHNICAL DATA

Part No	11732
Media	Fuels, solvents, Toulén, Ethanol, etc.
Capacity	50 l/min free flow
Air connection	3/8" (F) BSP
Maximum air pressure	0,7 (7) MPa (bar)
Maximum temperature	70 °C
Seals	Viton
Material pump body	Polypropylene
Material diaphragm	PTFE
Material balls	PTFE
Certification	ATEX
Connection	1/2" - 1/2" (F)-(F) BSP
Packaging LxWxH	0,22 x 0,22 x 0,22 m
Weight (Gross)	3,3 kg
H.S. Code	84135080



EUROLUBE EQUIPMENT

by Alentec & Orion AB, Grustagsvägen 4, SE-138 40 Älta, Sweden

EMAIL *eurolube@alentec.se

PHONE +46 (0)8-747 67 10

FAX +46 (0)8-715 20 74

 www.eurolube.com