



**DIGITAL PRE-SET METER /
DIGITAL MÄTARE, FÖRINSTÄLLBAR**



Digital pre-set oil meter, featuring a mechanism which, when activated, automatically shuts off the valve when the desired volume is reached.

- Simply and intuitive to use, it has a large display with 6 buttons
- Ergonomic four finger trigger with lock function
- Powered by 4 AA-batteries
- Light and robust, handle is made of cast aluminium and the display is surrounded by shock resistant TPE
- Several models with different outlets available to suit every application



Digital förinställbar oljemätare, med en mekanism som när den aktiveras, automatiskt stänger ventilen när önskad volym uppnås. Kan användas för olja och glykol.

- Enkel och intuitiv att använda, stor display med sex knappar
- Ergonomisk avtryckare med spärrfunktion
- Drivs av 4st AA-batterier
- Lätt och robust, handtag i gjuten aluminium och displayen är omgiven av stöttålig TPE
- Flera modeller med olika utlopp för att passa alla applikationer



10422 10452 10471 10472 10491

PART NO / ART.NR	OUTLET TYPE / UTLOPP
10422	Malleable hose, manual non-drip / formbar slang, manuell non-drip
10452	60° Rigid, manual non-drip / 60° rör, manuell non-drip
10471	90° hose, automatic non-drip / 90° slang, automatisk non-drip
10472	90° hose, manual non-drip / 90° slang, manuell non-drip
10491	135° hose, automatic non-drip / 135° slang, automatisk non-drip

TECHNICAL DATA

PART NO / ART.NR	10400, 10422, 10452, 10471, 10472, 10491
Inlet thread / inloppsgänga	1/2" BSP (F/Inv.)
Wetted parts materials / material i kontakt med vätska	Acetal, stainless steel, NBR, aluminum, brass, zinc plated steel / Acetal, rostfritt stål, NBR, aluminium, mässing, förzinkat stål
Meter type / typ av mätare	Oval gear / ovalhjul
Flowrate / flödes hastighet	1-30 l/min (0.25 - 7.5 US gal/min)
Maximum pressure / max arbetstryck	100 bar (1450 psi)
Temperature range / temperaturområde	-10 a 50 °C (14 a 122 °F)
Accuracy (oil) / noggrannhet (olja)	±0,5 %
Accuracy (coolant solutions) / noggrannhet (kylarvätska)	±1 %
Viscosity range / max viskositet	Up to 2000 mPa.s
Display / display	LCD with double row digits / LCD-display med dubbla rader
Units / enheter	Litres, gallons, quarts, pints
Batteries / batterier	4 x AA 1.5V
Weight (with nozzle and batteries) / vikt (med utloppsslang och batterier)	2.1 kg (4.6 lb)



EUROLUBE EQUIPMENT

by Alentec & Orion AB, Grustagsvägen 4, SE-138 40 Älta, Sweden

EMAIL eurolube@alentec.se

PHONE +46 (0)8-747 67 10

FAX +46 (0)8-715 20 74

www.eurolube.com